



# FUNCTIONAL SERVICING & STORMWATER MANAGEMENT REPORT

Dixie Mall Redevelopment

In Support of an Official Plan and Zoning By-Law Amendment



Report Prepared For:  
Slate Asset Management

Report Prepared By:



KWA Project No. 19410

April 12<sup>th</sup>, 2024

## Table of Contents

1.0	Introduction .....	1
1.1	Proposed Architectural Site Plan and Population Density.....	1
2.0	Study Parameters .....	2
3.0	Site Grading.....	2
3.1	Existing Site Grading .....	2
3.2	Proposed Site Grading .....	3
4.0	Sanitary Flow .....	3
4.1	Existing Sanitary Servicing .....	3
4.2	Existing Sanitary Flow .....	3
4.3	Sanitary Design Flow.....	4
4.4	Post-Development Sanitary Flow .....	4
4.5	Proposed Connection and Layout .....	5
5.0	Water Supply .....	5
5.1	Existing Water Servicing.....	5
5.2	Post-Development Water Demand.....	5
5.3	Proposed Connection and Layout .....	6
6.0	Stormwater Management .....	7
6.1	Pre-Development Drainage Conditions .....	7
6.2	Future MTO Improvements.....	7
6.3	Design Criteria .....	7
6.4	Allowable Release Rate.....	7
6.5	Post-Development Conditions .....	9
6.5.1	Drainage Directions .....	9
6.5.2	Runoff Quantity Control .....	9
6.5.3	Storm Sewer Design .....	11
6.5.4	Quality Control .....	11
6.5.5	Water Balance .....	12
7.0	Conclusion .....	14



## List of Tables

- Table 1: Land Use Summary
- Table 2: Proposed Sanitary Flows Summary
- Table 3: Water Demand
- Table 4: Summary of Modified Rational Method Calculations
- Table 5: Underground Storage Tanks
- Table 6: Orifice Plate Sizes
- Table 7: 5mm Water Balance Requirement

## List of Figures

- Figure 1 - Site Location Plan
- Figure 2 - Site Plan
- Figure 3 - Site Layout
- Figure 4 - General Servicing Plan
- Figure 5 - General Grading Plan
- Figure 6 - Sanitary Servicing Plan
- Figure 7 - Water Distribution Plan
- Figure 8 - Existing Drainage Plan
- Figure 9 - Stormwater Management Plan
- Figure 10 - Post-Development Drainage Plan

## List of Appendices

- Appendix A – Sanitary Demand Calculations
- Appendix B – Water Demand Calculations
- Appendix C – Stormwater Management Calculations

## 1.0 INTRODUCTION

KWA Site Development Consulting Inc. (“KWA”) has been retained by Slate Asset Management (“Slate”) to prepare this Functional Servicing & Stormwater Management Report in support of an Official Plan Amendment and Zoning By-Law Amendment (OPA/ZBA) application for the redevelopment of the north-west portion of the existing Dixie Outlet Mall located in the City of Mississauga, herein referred to as the “Site”. The municipal address is 1250 South Service Road.

The Site is 2.70 ha and is bound by South Service Road and QEW to the north, Haig Boulevard and residential lots to the west, residential lots to the south, and the existing Dixie Outlet Mall to the east. Refer to **Figure 1 – Site Location Plan**. The proposed development will require property ownership limits to be revised as a portion of the existing mall will be demolished to allow for future development blocks, and private and public roads. There is an existing 2.1m x 2.85m MTO box culvert that bisects the Dixie Outlet Mall property and conveys drainage to Applewood Creek. MTO is constructing a new interchange layout at Dixie Road. As part of this work, approximately 1.0 ha (2.5 acres) has been expropriated by the MTO along the South Service Road frontage which has reduced the overall property area of Dixie Outlet Mall and the existing box culvert will be twinned in the future.


### 1.1 PROPOSED ARCHITECTURAL SITE PLAN AND POPULATION DENSITY

Based on the proposed Site Plan from Giannone Petricone Architects dated March 26<sup>th</sup>, 2024, the 2.70 ha redevelopment proposal contemplates a total of six (6) blocks that can be described as follows. Refer to **Figure 2 – Site Plan** and **Figure 3 – Site Layout**.

- **Development Blocks:** There are 3 residential mid-rise and tower blocks (Blocks 1 – 3).
- **Future Municipal ROW:** There will be a future municipal right-of-way (ROW) off Haig Boulevard for access to the development and the existing Dixie Outlet Mall (Block 6).
- **Park Block:** There is a community park block (Block 4) along the west perimeter, directly south of the future ROW. There is an existing hydro easement within the block that continues east to the box culvert.
- **Easement Block:** Block 5 is an identified block which while owned by the client, has been used by adjacent neighbours and is currently developed with a residential use (i.e. residential rear yards with landscaping and accessory structures). This block is being created to provide a zoning reflecting existing conditions which match zoning on the balance of the residential lots. No new residential development is proposed and no changes to these lands are being proposed. Once this application is approved and this block exists, the applicant intends to explore the potential to engage the existing neighbours and explore transactional arrangements with regards to the limits of the identified block.

**Table 1: Land Use Summary**

Block	Land Use	Development	Total Area (ha)	Total Apartment
1	Residential	<i>Mid-Rise (8 Levels)</i>	0.56	159
2	Residential	<i>Tower (18 Levels) And Podium (6 Levels)</i>	0.68	338
3	Residential	<i>Two Towers (15+19 Levels) And Podium (6 Levels)</i>	0.71	500
4	Park		0.46	-
5	Easement		0.14	-
6	Future Municipal ROW		0.15	-
<b>TOTAL</b>			<b>2.70</b>	<b>997</b>




**KWA**  
SITE DEVELOPMENT CONSULTING INC.  
2453 Auckland Drive  
Burlington, ON L7L 7A9

REVISION BLOCK		
#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA

**SITE LOCATION PLAN**

SLATE ASSET MANAGEMENT

DIXIE MALL REDEVELOPMENT

MISSISSAUGA, ONTARIO

PROJECT No: 19410 | DRAWN BY: BC2 | CHECKED BY: CDB

NORTH ARROW



METRIC SCALE

N.T.S.

**FIGURE 1**



EXISTING RETAIL AUTO REPAIR


EXISTING DRIVEWAY

EXISTING NEIGHBOURHOOD

EXISTING DRIVEWAY

EXISTING NEIGHBOURHOOD


HAIG BOULEVARD  
DEDICATED BY REGISTERED PLAN 305  
HAIG BLVD



All drawings, specifications, related documents and design are the copyright property of the architect and must be returned upon request. Reproduction of the drawings, specifications, related documents and design in whole or in part is strictly forbidden without the architect's written permission.

Revision	Date
5	2024.03.26
3	2022.12.16

Revision	Date
5	2024.03.26
3	2022.12.16



**giannone petricone associates**

Giannone Petricone Associates Inc. Architects  
96 Spadina Avenue, Toronto, Canada M5V 2J6  
T 416.591.7788 F 416.591.1293 E mail@gpa.ca

**DIXIE MALL REDEVELOPMENT**  
1250 South Service Road  
Mississauga, ON L5E 3E5

**SITE PLAN**  
**FIG 2 - SITE PLAN**

DRAWN BY:	MH
CHECKED BY:	AV
PROJECT START DATE:	06/28/22
PROJECT NO.:	22138
SHEET NUMBER	

**A100**



QUEEN ELIZABETH WAY

SOUTH SERVICE ROAD

PROPOSED VEHICULAR ACCESS

MTO SETBACK GREENLAND  
± 0.32 HA.  
± 0.79 ACRE

14m MTO SETBACK

**BLOCK 2**

± 0.68 HA.  
± 1.69 ACRE

NET DEVELOPMENT AREA  
± 0.68 HA.  
± 1.69 ACRE

**BLOCK 3**

± 0.71 HA.  
± 1.77 ACRE

NET DEVELOPMENT AREA  
± 0.45 HA.  
± 1.11 ACRE

8 m

SANITARY AND WATERMAIN EASEMENT  
(± 0.43 HA.)  
(± 1.06 ACRE)

SANITARY/  
WATERMAIN  
EASEMENT

± 0.56 HA.  
± 1.38 ACRE

NET DEVELOPMENT AREA  
± 0.52 HA.  
± 1.29 ACRE

**BLOCK 1**

HAIG BLVD

PROPOSED SANITARY/  
WATERMAIN  
EASEMENT

PROPOSED FUTURE  
MUNICIPAL ROW

**DIXIE MALL**

EXISTING MALL PARKING

EXISTING  
CULVERT  
EASEMENT

**BLOCK 4**

PUBLIC  
PARK  
PARK AREA  
± 0.45 HA.  
± 1.11 ACRE

EXISTING MALL PARKING

VEHICULAR CONNECTION TO  
EXISTING PARKING LAYOUT

EXISTING HYDRO EASEMENT  
(± 0.11 HA.)  
(± 0.27 ACRE)

9 m

**BLOCK 5**

0.14 HA  
0.36 ACRE

PARCEL APPROX. LINE


EXISTING NEIGHBOURHOOD

All drawings, specifications, related documents and design are the copyright property of the architect and must be returned upon request. Reproduction of the drawings, specifications, related documents and design in whole or in part is strictly forbidden without the architect's written permission.

Revision Date

5 ISSUE FOR ZBA/OPA RESUBMIT 2024.03.26  
3 ISSUED FOR ZBA/OPA 2022.12.16

Revision Date



**giannone  
petricone  
associates**

Giannone Petricone Associates Inc. Architects  
96 Spadina Avenue, Toronto, Canada M5V 2J6  
T 416.591.7788 F 416.591.1293 E mail@gpaia.com

**DIXIE MALL  
REDEVELOPMENT**  
1250 South Service Road  
Mississauga, ON L5E 3E5

**BLOCK PLAN  
FIG 3 - SITE LAYOUT**

DRAWN BY: MH  
CHECKED BY: AV  
PROJECT START DATE: 06/28/22  
PROJECT NO.: 22138  
SHEET NUMBER

**A017**

PLOT DATE: 2024-04-17 5:22:47 PM

1 BLOCK PLAN  
A017 1:500



As per Region of Peel's criteria of 2.7 persons/ unit, the expected total population for the redevelopment of 997 apartment units is **2692 people**.

## **2.0 STUDY PARAMETERS**

This Functional Servicing and Stormwater Management Report has been prepared in coordination and with regard to the following documents and drawings:

- Architectural Plans prepared by Giannone Petricone Associates
- Planning Reports prepared by Glen Schnarr & Associates
- Landscape Design by Janet Rosenberg & Studio
- Transportation Report by LEA Associates
- Topographic Survey by R. Avis Surveying Inc.
- Subsurface Utility Engineering Mapping Services by T2 Utility Engineers
- Geotechnical and Hydrogeological Report by Grounded Engineering
- Region of Peel Linear Wastewater Standards March 2023
- Region of Peel Public Works Design, Specifications and Procedures Manual Linear Infrastructure – Watermain Design Criteria June 2010
- Region of Peel Public Works Design, Specifications and Procedures Manual Linear Infrastructure – Functional Servicing and Storm Water Management Report Nov. 2009
- Region of Peel 2020 Water & Wastewater Master Plan for the Lake-Based System Volume 3
- City of Mississauga Transportation & Works Department Section 8 – Storm Drainage Design Requirements January 2020
- City of Mississauga Transportation & Works Department Section 2 – Design Requirements Manual September 2016.
- Credit Valley Conservation Stormwater Management Criteria, August 2012
- Credit Valley Conservation and Toronto and Region Conservation Authority Low Impact Development Stormwater Management Planning and Design Guide – Version 1.0 2011
- Ministry of Environment Stormwater Management Planning and Design Manual March 2003
- Ministry of Environment's Design Guidelines for Drinking-Water Systems 2008
- Region of Peel Record Drawings of Haig Boulevard and South Service Road

## **3.0 SITE GRADING**

### **3.1 EXISTING SITE GRADING**

A topographical survey was completed by R. Avis Surveying Inc. in May 2019 which indicated that the Site generally slopes to the south. This can be attributed to the Applewood Creek on the east side of the Site that drains in a southerly direction towards Lakeview Golf Course. There are catch basins within the parking lot which connect to the existing 2.1 x 2.85 m box culvert at multiple locations. The box culvert conveys flows from the east tributary of the Applewood Creek from the north side of the QEW at Harvest Drive, across the highway, and southwesterly through the Mall property under the existing mall structure and eventually discharging into the open creek system. The north parking lot storm flows are captured and connect into the box culvert underneath the existing Mall. The west and south parking lot flows outlet directly into the Applewood Creek.

## 3.2 PROPOSED SITE GRADING

The proposed grading plan consists of grades along the Site perimeter area and along the building footprint in the development blocks. Grading is generally governed by the existing boundary conditions. The grading along Private Street A to the north of the existing mall is dictated by the grades in the existing parking lot, perimeter grades of the mall, and catch basins at low points. Access for the 20 m future municipal ROW is provided off Haig Boulevard. The MTO setback areas within Blocks 2 and 3 will drain north towards South Service Road. The proposed grading plan considers the storm outlet elevations, finished floor elevations, parking lot slopes, major overland flow paths, adequate cover over proposed services, and private street alignment. Generally, the development (except Block 3) slopes to the south-east towards a connection into the box culvert. There is a high point at the corner of Private Street A. An existing storm connection to the culvert is utilized for Block 3 and adjacent street drainage. Detailed grading design for the development blocks, future municipal ROW, and park blocks will be completed during the Site Plan Approval process.

Refer to **Figure 4 – General Servicing Plan** and **Figure 5 – General Grading Plan** for the proposed conceptual grading to support the OPA/ZBA application.

## 4.0 SANITARY FLOW

### 4.1 EXISTING SANITARY SERVICING

An existing 900mm/1050mm reinforced concrete trunk sanitary sewer draining south is located on Haig Boulevard. An existing 1200mm reinforced concrete trunk sanitary sewer draining south is located on Dixie Road. The sanitary flows from the existing Mall (including the existing No Frills grocery store to the south) are currently pumped to the Haig Boulevard sanitary trunk sewer and ultimately drain to the Region of Peel's G.E. Booth Lakeview Wastewater Treatment Plant located south of Lakeshore Road East, approximately 2.2 km south of the Site. Ongoing expansion and retrofit work at the G.E. Booth Wastewater Treatment Plant is shown in the Region's Capital Budget for the next 10+ years.

As per correspondence with the Region of Peel, sanitary sewer construction is set to begin on Haig Boulevard in Spring 2024 and to be completed in 2026. The existing 900 mm sanitary trunk sewer will be replaced by a new 900 mm trunk sewer. Also, a 450 mm sanitary sewer will be installed, which is in parallel with the newly constructed 900 mm trunk sewer near the Subject Site and ultimately connects into the new 900 mm sanitary sewer downstream. Refer to Ministry of Transportation *drawing # 420H (WS-20) and 421D (WS-21)* dated February 2022 in **Appendix A**, that shows the sanitary sewer connection into the Haig Boulevard trunk sewer.




### 4.2 EXISTING SANITARY FLOW

The Site is currently zoned commercial. Sanitary flows for the entire Mall outlet to the 900mm Haig Boulevard trunk sewer. Using the following Region of Peel's Linear Wastewater Standards (2023), the theoretical existing commercial sanitary flow draining to the Haig Boulevard sewer is determined to be **17.14 L/s**.

- Population Density: Commercial = 50 persons/ha
- Peaking Factor = Calculated using the Harmon Formula
- Design Flow = 270 Litres / capita / day (for non-residential flow)
- Infiltration Flow + Foundation Drains= 0.00028 m<sup>3</sup>/s/ha (0.28 L/s/ha)





# SOUTH SERVICE ROAD



LEGEND	
	PROPOSED STORM SEWER
	PROPOSED STORM MANHOLE
	PROPOSED AREA DRAINS (BY OTHERS)
	PROPOSED CATCHBASIN
	EXISTING BOX CULVERT
	EXISTING STORM SEWER
	EXISTING STORM MANHOLE
	EXISTING STORM CATCHBASIN MANHOLE
	EXISTING CATCHBASIN
	EXISTING DOUBLE CATCHBASIN
	PROPOSED SANITARY SEWER
	PROPOSED SANITARY MANHOLE
	EXISTING SANITARY SEWER
	EXISTING SANITARY TRUNK (> 600mm)
	EXISTING SANITARY MANHOLE
	PROPOSED WATERMAIN
	EXISTING WATERMAIN
	EXISTING VALVE AND BOX
	PROPOSED UTILITY CORRIDOR ALLOWANCE
	APPROXIMATE LIMITS OF FLOOD HAZARD (AS PER 2017 CVC APPLEWOOD CREEK MAPPING SHEET 3)

REVISION BLOCK		
#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA



BENCHMARK NOTE:  
ELEVATIONS SHOWN ARE GEODETIC  
AND ARE REFERRED TO CITY OF  
MISSISSAUGA BENCH MARK NO. 72,  
HAVING AN ELEVATION OF 106.72m

**GENERAL SERVICING PLAN**  
 SLATE ASSET MANAGEMENT  
**DIXIE MALL**  
 MISSISSAUGA, ONTARIO  
 PROJECT NO. 18-10 | DRAWN BY: BC2 | CHECKED BY: CCB

**FIGURE 4**



NOTES:  
• ALL DIMENSIONS AND ELEVATIONS IN METERS




# SOUTH SERVICE ROAD

(LINEWORK, CENTRELINE, AND PROPERTY LINE ELEVATIONS  
AREA AS PER MTO DESIGN DRAWINGS PROVIDED 20210305)

REVISION BLOCK		
#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA




BENCHMARK NOTE:  
ELEVATIONS SHOWN ARE GEODETIC  
AND ARE REFERRED TO CITY OF  
MISSISSAUGA BENCH MARK NO. 72,  
HAVING AN ELEVATION OF 109.72m



**GENERAL GRADING PLAN**  
 SLATE ASSET MANAGEMENT  
**DIXIE MALL**  
 MISSISSAUGA, ONTARIO  
 PROJECT NO. 18410 DRAWN BY: BGC2 CHECKED BY: CCB

**FIGURE 5**



LEGEND	
<span style="color: red;">x</span> 100.00	PROPOSED PAVEMENT ELEVATION
<span style="color: red;">-</span> 100.00	PROPOSED PAVEMENT CHAINAGE & ELEVATION
<span style="color: red;">-</span> 100.00	PROPOSED PAVEMENT (HIGH POINT/LOW POINT ELEVATION)
<span style="color: grey;">-</span> 100.00	EXISTING PAVEMENT CHAINAGE & ELEVATION
<span style="color: red;">x</span> 100.00(S/W)	PROPOSED SWALE CENTRELINE ELEVATION
<span style="color: red;">x</span> 100.00(EV)	PROPOSED ELEVATION TO MATCH EXISTING ELEVATION
<span style="color: red;">x</span> 100.00(MTO)	PROPOSED MTO DESIGN ELEVATION FOR SOUTH SERVICE ROAD REALIGNMENT AS PER DRAWING PROVIDED ON 030521
<span style="color: green;">o</span>	PROPOSED STORM MANHOLE
<span style="color: green;">□</span>	PROPOSED CATCHBASIN
<span style="color: green;">□</span>	PROPOSED AREA DRAIN (BY OTHERS)
<span style="color: green;">o</span>	EXISTING STORM MANHOLE
<span style="color: grey;">□</span>	EXISTING CATCHBASIN
<span style="color: grey;">□</span>	EXISTING DOUBLE CATCHBASIN
<span style="color: red;">o</span>	PROPOSED SANITARY MANHOLE
<span style="color: grey;">o</span>	EXISTING SANITARY MANHOLE
<span style="color: grey;">o</span>	EXISTING HYDRANT
<span style="color: grey;">o</span>	EXISTING VALVE AND BOX
<span style="color: grey;">o</span>	EXISTING CONTOUR
<span style="color: orange;">-</span>	APPROXIMATE LIMITS OF FLOOD HAZARD (AS PER 2017 CVC APPLEWOOD CREEK MAPPING SHEET 3)
<span style="color: red;">→</span>	PROPOSED OVERLAND FLOW DIRECTION ALONG CENTRELINE
<span style="color: grey;">→</span>	MAJOR OVERLAND FLOW DIRECTION

NOTES:  
• ALL DIMENSIONS AND ELEVATIONS IN METERS



Based on correspondence with the Operations Supervisor at the Dixie Outlet Mall, the existing flow rate for the pump house near the existing No Frills is approximately 148 US Gallons/Minute = 9.3 L/s. The pumped flow connects into a gravity sanitary sewer, collecting flows from the existing Mall, and discharges into the Haig Boulevard sanitary trunk sewer.

Refer to *City of Mississauga drawing # 86042-1* dated June 1986 in **Appendix A**, that shows the sanitary sewer connection into the Haig Boulevard trunk sewer. Also, refer to **Appendix A** for Existing Commercial Sanitary Calculations.

### 4.3 SANITARY DESIGN FLOW

The sanitary design flows and population density for the Site have been calculated based on the Region of Peel’s Linear Wastewater Standards (2023). The relevant design criteria are summarized below:

- Population Density: Apartments = 2.7 persons/unit
- Peaking Factor = Calculated using the Harmon Formula
- Design Flow = 290 Litres / capita / day (for residential flow)
- Infiltration Flow + Foundation Drains= 0.00028 m<sup>3</sup>/s/ha (0.28 L/s/ha)R

### 4.4 POST-DEVELOPMENT SANITARY FLOW

The proposed development will outlet into the new 450 mm sanitary sewer on Haig Boulevard, which ultimately outlets to the 900 mm sanitary sewer on Haig Boulevard. The connection to the Haig Boulevard sewer is preferred as connecting into the Dixie Road sewer would require crossing the MTO box culvert that bisects the Site, which is not feasible given the sanitary trunk sewer elevations on Dixie Road.

Refer to Table 2 for sanitary flows summary.

**Table 2: Proposed Sanitary Flows Summary**

Draft Plan Blocks	Total Area (ha)	Total Population	Average Flow (L/s)	Peaking Factor	Peak Flow	Infiltration (L/s)	Total Sanitary Flow (L/s)
<b>1, 2 &amp; 3 (Development)</b>	1.95	2692	9.04	3.48	31.46	0.55	32.01
<b>4, 5, &amp; 6 (Park, Easement &amp; ROW)</b>	0.75	0	0	0	0	0.21	0.21
<b>TOTAL</b>	<b>2.70</b>	<b>2692</b>	<b>9.04</b>	<b>3.48</b>	<b>31.46</b>	<b>0.76</b>	<b>32.22</b>

The existing 19.6 ha Dixie Outlet Mall development has sanitary flows of 17.1 L/s draining to the Haig Boulevard sewer. The 2.7 ha of the redevelopment will have sanitary flows of **32.22 L/s**, whereas the remaining 16.90 ha of the Dixie Outlet Mall development will have sanitary flows of 14.9 L/s.

The sanitary sewer flows outletting to Haig Boulevard will increase by **30 L/s** (47.1 – 17.1) over pre-development conditions. As per correspondence with the Region of Peel, sanitary flows from the development and existing Dixie Outlet Mall can connect into the new 450 mm sewer on Haig Boulevard (refer to **Appendix A**).



It is important to note that the calculated population density based on a 2.7 persons/unit is conservative, resulting in conservative estimates of sanitary flow. For the entire Site, there are approximately 65% 1-bedroom units, 20% 2-bedroom units, and 15% 3-bedroom units proposed. A large proportion of the suite type contemplated at this stage is 1-bedroom units.

## 4.5 PROPOSED CONNECTION AND LAYOUT

Blocks 1, 2, and 3 will be serviced by 300mm sanitary sewers along Private Street A. All Site flows will outlet to the 375mm sanitary sewer along the future municipal ROW in Block 6, which will connect to the new 450 mm municipal sewer flowing at 0.155% on Haig Boulevard.

The 14.9 L/s of sanitary flows from the remaining Dixie Outlet Mall Site will be conveyed from the existing manhole MH63 (east of box culvert) to the 450 mm sewer on Haig Boulevard.

Refer to **Figure 6 – Sanitary Servicing Plan**. Refer to **Appendix A** for detailed sanitary calculations.

## 5.0 WATER SUPPLY

### 5.1 EXISTING WATER SERVICING

The existing water infrastructure adjacent to the Site consists of a 400mm watermain on Dixie and a 200mm watermain on Haig Boulevard. The 300mm watermain on South Service Road has recently been abandoned and a new 400 mm waterman has been installed and commissioned. The Site obtains treated water from Arthur P. Kennedy Water Treatment Plant located south of Lakeshore Boulevard East, approximately 3.5 km south of the Site. This plant is operated by the Ontario Clean Water Agency (OCWA) on behalf of the Region of Peel. The Region owns and operates the water distribution system. The Site is within the Region's central trunk system and Pressure Zone 1 (also denoted as CT1). Elevations in this pressure zone range from the Lake Ontario at 75.0m to 106.7m. The proposed Site elevation is approximately 102.0m to 106.0m.

As per the Region of Peel Water and Wastewater Master Plan, there are two transmission mains within the CT1 starting from the A.P. Kennedy WTP and delivering water to the Silverthorn Reservoir: a 900-mm diameter transmission main and a 1500-mm diameter transmission main. The total theoretical Pressure Zone 1 central transmission capacity is approximately 342 ML/d. However, the actual capacity is estimated at approximately 279 ML/d. The total reservoir capacity at the A.P. Kennedy WTP is 25 ML.

Existing hydrants surrounding the Dixie Outlet Mall are located on the east and west sides of Dixie Road, south side of South Service Road and west side of Haig Boulevard. Existing hydrants are located within the Mall along the fire access route.

### 5.2 POST-DEVELOPMENT WATER DEMAND

The domestic and fire water demand for the Site was calculated based on the Region of Peel's Public Works Watermain Design Criteria. The relevant design criteria are summarized below:


- Average Daily Demand: Residential = 280 Litres / capita / day
- Max Day Factor: Residential = 2.0
- Peak Hour Factor: Residential = 3.0



# SOUTH SERVICE ROAD

# HAIG BOULEVARD


# MYRON DRIVE




## REVISION BLOCK

#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA

KWA SITE DEVELOPMENT  
 2455 Appleland Drive  
 Burlington, ON L7L 7A9



BENCHMARK NOTE:  
 ELEVATIONS SHOWN ARE GEODETIC  
 AND ARE REFERRED TO CITY OF  
 MISSISSAUGA BENCH MARK NO. 72,  
 HAVING AN ELEVATION OF 106.72m



**SANITARY SERVICING PLAN**  
 SLATE ASSET MANAGEMENT  
**DIXIE MALL**  
 MISSISSAUGA, ONTARIO  
 PROJECT No: 18410 | DRAWN BY: BGC2 | CHECKED BY: CCB

## FIGURE 6

NOTES:  
 • ALL DIMENSIONS AND ELEVATIONS IN METERS



Fire Demand is based on MOE Design Guidelines for Drinking-Water Systems. The suggested fire flow for an equivalent population of 2692 would be **105 L/s** (interpolated using Table 8-1: Fire Flow Requirements).

The Region of Peel strives to maintain a minimum operation pressure of 275 kPa (40 psi) and maximum operating pressure of 690 kPa (100 psi).

The detailed water demand calculations can be found in **Appendix B** and are summarized in the Table below.

**Table 3: Water Demand**

<b>Draft Plan Blocks</b>	<b>Population</b>	<b>Average Daily Demand (L/s)</b>	<b>Max Daily Demand (L/s)</b>	<b>Peak Hour Demand (L/s)</b>
<b>1</b>	429	1.39	2.78	4.17
<b>2</b>	913	2.96	5.92	8.87
<b>3</b>	1350	4.38	8.75	13.13
<b>4</b>	0	0	0	0
<b>5</b>	0	0	0	0
<b>6</b>	0	0	0	0
<b>TOTAL</b>	<b>2692</b>	<b>8.72</b>	<b>17.45</b>	<b>26.17</b>

The post-development water demands are as follows:

- Domestic Supply Line – Peak Hour Demand = **26.17 L/s**
- Maximum Fire Flow Demand + Max Daily Demand = **122.45 L/s**

A fire hydrant test was completed in November 2022 by Troy Life & Fire Safety Ltd. The static hydrant was located at the corner of South Service Road and the north Mall entrance, and the flow hydrant was located at the corner of South Service Road and Haig Boulevard. This testing indicated a static water pressure of 64 psi and theoretical fire flow of 6746 USGPM (426 L/s) at a residual pressure of 20 psi. There is sufficient pressure and flow in the municipal system to provide the required demands of the proposed development. A fire hydrant test along Haig Boulevard has been initiated and will be completed in Spring 2024.

### **5.3 PROPOSED CONNECTION AND LAYOUT**


Blocks 1, 2, and 3 will be serviced by 300mm watermains that will connect to the new 400mm watermain on South Service Road and the existing 200mm watermain on Haig Boulevard. The connection to South Service Road will be provided adjacent to Building C and the connection to Haig Boulevard will be along the future municipal ROW. Refer to **Figure 7 – Water Distribution Plan**.

Backflow prevention valves and chambers will be required at each municipal connection and confirmed during detailed design in the Site Plan Application. Hydrants are proposed within 45m of the buildings' Fire Department Connection (FDC) and the distance will be confirmed during the individual Site Plan Applications.

A **Multi-Use Demand table** is requested by the Region to fulfil the modelling requirements and determine the proposals impact to the existing system. Refer to **Appendix B** for the completed Multi-Use Demand table.




# SOUTH SERVICE ROAD




REVISION BLOCK		
#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA

KWA SITE DEVELOPMENT  
 2455 Ashland Drive  
 Burlington, ON L7L 7A9

NORTH ARROW



BENCHMARK NOTE:  
 ELEVATIONS SHOWN ARE GEODETIC  
 AND ARE REFERRED TO CITY OF  
 MISSISSAUGA BENCH MARK NO. 72,  
 HAVING AN ELEVATION OF 106.72m



**WATER DISTRIBUTION PLAN**  
 SLATE ASSET MANAGEMENT  
**DIXIE MALL**  
 MISSISSAUGA, ONTARIO  
 PROJECT NO: 18410 | DRAWN BY: BGC2 | CHECKED BY: CCB

**FIGURE 7**

NOTES:  
 • ALL DIMENSIONS AND ELEVATIONS IN METERS



## 6.0 STORMWATER MANAGEMENT

### 6.1 PRE-DEVELOPMENT DRAINAGE CONDITIONS

The Site generally slopes in the south direction. The Site is primarily impervious consisting of mall rooftop areas and associated asphalt parking lot areas. There is an existing 2.1m x 2.85m box culvert that bisects the Dixie Outlet Mall property to convey drainage from north of the QEW to Applewood Creek. This culvert also collects runoff from the on-site private storm sewers. It currently runs through the parking lot and beneath the existing mall.

### 6.2 FUTURE MTO IMPROVEMENTS

MTO is constructing a new interchange layout at Dixie Road. The South Service Road will be realigned to accommodate the new interchange and to allow for directional access at Dixie Road and the QEW. As part of this work, MTO is proposing the existing box culvert be converted to a twinned box culvert outletting to the Applewood Creek. The twinned box culvert will be on east side of existing box culvert and will not form part of or encroach Phase 1 of the proposed development.

### 6.3 DESIGN CRITERIA

The following guidelines have been specified in the City of Mississauga's Development Requirements Manual:

Water Quantity Control: For the Applewood Creek Subwatershed, 100-yr post-development flows must be controlled to the 2-yr pre-development flows. For pre-development lands, it is implied as raw land for which the runoff coefficient is equal to 0.25 but will not exceed 0.50 for a site that is already developed.

Water Quality Control: Enhanced (Level 1) protection through the removal of 80% of total suspended solids (TSS) is required.

Water Balance: The first 5mm of runoff shall be retained on-site and managed by way of infiltration, evapotranspiration, re-use or filtration.

### 6.4 ALLOWABLE RELEASE RATE

The proposed development consists of 6 blocks with total area of 2.70 ha. Runoff from the blocks will be directed to the existing box culvert. The proposed drainage areas loosely align with the block boundaries but also include future anticipated development areas and exclude MTO setback lands that will drain towards South Service Road. The following four outlets (two existing and two new) will ensure that stormwater runoff is conveyed to the box culvert. Refer to the **Figure 8 – Existing Drainage Plan**, **Figure 9 – Stormwater Management Plan** and **Figure 10 – Post-Development Drainage Plan**.

#### **Existing Culvert Outlet (Outlet #1)**

The drainage area of 1.44 ha labelled as 'EXIST' drains to Outlet #1. This includes Block 4 (park), Block 5 (easement), and unaltered parking lot area that drains to this outlet in the existing condition. In the pre-development condition, this outlet receives drainage from a larger paved area (1.68 ha) having a higher runoff coefficient of 0.90. There are existing orifice controls within the existing storm sewers, with the downstream 150 mm orifice tube controlling the catchment area release rate to 109 L/s (refer to City of Mississauga drawing No. 86042-I). In the post-development condition, a park block is added and the existing parking lot and storm infrastructure is maintained. Since the drainage area and runoff coefficient are reduced in the proposed condition, the peak flows will decrease for every storm event.



# SOUTH SERVICE ROAD

APPROXIMATE CENTRELINE OF PAVEMENT

APPROXIMATE CENTRELINE OF PAVEMENT

## HAIG BOULEVARD

EX STM MH75  
A=1.58  
C=0.90

DRAINAGE AREA WITHIN  
EX STM MH75 (1.58ha)  
WHICH IS CAPTURED BY  
EX STM CB32


EX STM MH80  
A=0.11  
C=0.90

EX CB 32  
A=0.32  
C=0.90


EX STM MH61  
A=1.68  
C=0.85

## MYRON DRIVE

REVISION BLOCK		
#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA



BENCHMARK NOTE:  
ELEVATIONS SHOWN ARE GEODETIC  
AND ARE REFERRED TO CITY OF  
MISSISSAUGA BENCH MARK NO. 72,  
HAVING AN ELEVATION OF 108.72m



**LEGEND**

- EX STM MH80  
A=0.11  
C=0.90
- DRAINAGE ID
- EXISTING DRAINAGE AREA
- EXISTING RUNOFF COEFFICIENT
- ST — EXISTING STORM SEWER
- EXISTING STORM MANHOLE
- EXISTING STORM CATCHBASIN MANHOLE
- EXISTING CATCHBASIN
- EXISTING DOUBLE CATCHBASIN
- ➔ MAJOR OVERLAND FLOW DIRECTION

**EXITING DRAINAGE PLAN**  
SLATE ASSET MANAGEMENT  
**DIXIE MALL**  
MISSISSAUGA, ONTARIO  
PROJECT NO: 18410 | DRAWN BY: BC2 | CHECKED BY: CCB

**FIGURE 8**


NOTES:  
ALL DIMENSIONS AND  
ELEVATIONS IN METERS



# SOUTH SERVICE ROAD

**HAIG BOULEVARD**

REVISION BLOCK		
#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA



Block ID	Storage Required (m <sup>3</sup> )	Tank Depth/ Acting Head (m)	Orifice Plate Invert (m)	Orifice Size (mm)	Release Rate (m <sup>3</sup> /s)
<b>OUTLET #2</b>					
STREET+ BLD A	188	2.0	100.33	130	0.052
BLD B	148	2.0	100.46	115	0.041
PKNG	103	0.5	100.25	140	0.028
FUT. ROW#1	54	2.5	99.52	200	0.136
<b>OUTLET #4</b>					
BLD C + EXT2	145	3.0	100.29	100	0.040
<b>TOTAL</b>	<b>639</b>				<b>0.176</b>

<sup>1</sup> As per the section views of the Site Plan, parking (P1) level is 5 m high. Considering the Building FFEs, the slab thickness, and the presence of exposed foundations, 2 - 3 m is approximated as the available storage tank depth for the tanks proposed in the parking levels. For the tanks proposed under parking lots or within the ROW, the depth is approximated based on the proposed surface grades, tank inverts, and typical cover for pavement.

<sup>2</sup> The storage tank for 'FUT. ROW' is located along the storm sewers that drain to Outlet #2. The orifice downstream of this tank (at MH2) will receive controlled flows from Building A ('BLD A'), Building B ('BLD B'), a portion of Private Street A ('STREET') and parking area ('PKNG'). The orifice will restrict peak flows to 136 L/s for the total drainage area of 1.63 ha.


**LEGEND**

- PROPOSED STORM MANHOLE
- DRAINAGE AREA OUTLET#
- DRAINAGE AREA (ha)
- RUNOFF COEFFICIENT
- DRAINAGE AREA LIMIT
- PROPOSED STORM SEWER
- PROPOSED CATCHBASIN
- EXISTING 2.1m x 2.85m BOX CULVERT
- PROPOSED PROPERTY BOUNDARY
- EXISTING STORM SEWER
- EXISTING STORM MANHOLE
- EXISTING CATCHBASIN
- PROPOSED MAJOR FLOW PATH
- EXISTING CONTOUR

KWA  
SITE DEVELOPMENT  
2455 Appleton Drive  
Burlington, ON L7L 7A9

NORTH ARROW

BENCHMARK NOTE:  
ELEVATIONS SHOWN ARE GEODETIC  
AND ARE REFERRED TO CITY OF  
MISSISSAUGA BENCH MARK NO. 72,  
HAVING AN ELEVATION OF 106.70m



**STORMWATER MANAGEMENT PLAN**

SLATE ASSET MANAGEMENT

**DIXIE MALL**  
MISSISSAUGA, ONTARIO

PROJECT NO: 18/19 | DRAWN BY: BC2 | CHECKED BY: CCB

**FIGURE 9**


NOTES:  
• ALL DIMENSIONS AND ELEVATIONS IN METERS UNLESS STATED OTHERWISE



# SOUTH SERVICE ROAD

# HAIG BOULEVARD

REVISION BLOCK		
#	DATE	DESCRIPTION
1	12/06/22	ISSUED FOR ZBA
2	04/12/24	ISSUED FOR ZBA




**LEGEND**

- 101 A=0.21 C=0.90 (Drainage Area ID)
- (Drainage Area Limit)
- (Proposed Storm Sewer)
- (Proposed Catchbasin)
- (Existing 2.1m x 2.85m Box Culvert)
- (Proposed Property Boundary)
- (Existing Storm Sewer)
- (Existing Storm Manhole)
- (Existing Catchbasin)
- (Proposed Major Flow Path)
- (Existing Contour)

**METRIC SCALE**  
0 15 Metres  
1:500

NEW PROPOSED BOX CULVERT TIE-IN LOCATION PER MTO FILE RECEIVED ON MARCH 5, 2021



BENCHMARK NOTE: ELEVATIONS SHOWN ARE GEODETIC AND ARE REFERRED TO CITY OF MISSISSAUGA BENCH MARK NO. 72, HAVING AN ELEVATION OF 106.72m

CHECKED BY: CCB

POST DEVELOPMENT DRAINAGE PLAN  
SLATE ASSET MANAGEMENT  
DIXIE MALL  
MISSISSAUGA, ONTARIO  
PROJECT NO: 18/19  
DRAWN BY: BC2

FIGURE 10

NOTES:  
• ALL DIMENSIONS AND ELEVATIONS IN METERS UNLESS STATED OTHERWISE



Refer to **Figure 8 – Existing Drainage Plan** and **Figure 9 – Stormwater Management Plan** for the changes in the drainage area to Outlet #1.

### **Proposed Culvert Outlet (Outlet #2)**

Flows from Building A ('BLD A'), Building B ('BLD B'), a portion of Private Street A ('STREET'), Block 6 consisting of future municipal ROW ('FUT.ROW') and future development area ('PKNG') are directed to Outlet #2, resulting in a total drainage area of 1.63 ha. In the pre-development condition, this area was occupied by parking lots or existing mall rooftop.

The pre-development flow rates for the proposed area are determined using the Rational Method. The inputs area:

- Drainage Area to Culvert = 1.63 ha
- Time of Concentration: 15 minutes
- Pre-development Runoff Coefficient (C): 0.5 as per City of Mississauga's Development Requirements Manual
- Intensity (i): 60 mm/hr for a 2-yr storm event based on a = 610, b = 4.6, c = 0.78 as per City of Mississauga's Development Requirements Manual

$$Q = CiA = 0.5 * 60 \text{ mm/hr} * 1.63 \text{ ha}$$

$$Q = 0.136 \text{ m}^3/\text{s}$$

The 2-year pre-development flow for the area is **0.136 m<sup>3</sup>/s**.

Quantity control is to be provided individually for each development block. Drainage for the Private Street A is combined with the flows from Building A and the storage required for both drainage areas is provided in one storage tank. The release rates are proportionally assigned for the blocks according to their areas. Given total flow of 0.136 m<sup>3</sup>/s and drainage area of 1.63 ha, the resulting unit rate is **83.2 L/s/ha**.

### **Existing Culvert Outlet (Outlet #3)**

The drainage area of 0.22 ha labelled as 'EX104' drains to Outlet #3. This includes a portion of Private Street A and existing parking spaces. In the pre-development condition, this outlet received drainage from a larger paved area (0.32 ha) through existing CB24, CB32, and DCB31. In the post-development condition, CB24 will be abandoned and CB32 and DCB31 will capture flows within the catchment area. Since the flows have decreased in the proposed condition for every storm event, no storage is proposed in drainage area 'EX104'. Refer to **Figure 8 – Existing Drainage Plan** and **Figure 9 – Stormwater Management Plan** for the changes in the drainage area to Outlet #3.

### **Proposed Culvert Outlet (Outlet #4)**

Flows from Building C ('BLD C') and a portion of Private Street A ('EXT2') are directed to Outlet #4, resulting in a total drainage area of 0.48 ha. In the pre-development condition, this area was occupied by parking lots or drive aisles.

The pre-development flow rates for the proposed area are determined using the Rational Method. The inputs area:

- Drainage Area to Culvert = 0.48 ha
- Time of Concentration: 15 minutes
- Pre-development Runoff Coefficient (C): 0.5 as per City of Mississauga's Development Requirements Manual
- Intensity (i): 60 mm/hr for a 2-yr storm event based on a = 610, b = 4.6, c = 0.78 as per City of Mississauga's Development Requirements Manual

$$Q = CiA = 0.5 * 60 \text{ mm/hr} * 0.48 \text{ ha}$$

$$Q = 0.040 \text{ m}^3/\text{s}$$

The 2-year pre-development flow for the area is **0.040 m<sup>3</sup>/s**.

Quantity control is provided within Building C. The release rate must be less than 0.040 m<sup>3</sup>/s for the drainage area of 0.48 ha, resulting in the unit rate is **83.2 L/s/ha**.

Additionally, some areas from Blocks 2 and 3 are dedicated to the MTO setback areas labelled as 'MTO1' and 'MTO2'. Refer to **Figure 10 – Post-Development Drainage Plan**.

## 6.5 POST-DEVELOPMENT CONDITIONS

### 6.5.1 DRAINAGE DIRECTIONS

The proposed development contains stormwater sewers along the Private Street A and the future municipal ROW. There are also existing storm sewers along the north-east corner and along the south of the property that will be utilized. In total, there are four storm outlets into the box culvert within the subject Site. The layout of the storm sewers is depicted in **Figure 9 – Stormwater Management Plan**.

### 6.5.2 RUNOFF QUANTITY CONTROL

For drainage areas 'EXIST' and 'EX104', the flows are expected to decrease in the proposed condition for every storm event; therefore, no storage is proposed to control the drainage in these areas. For Outlets #2 and #4, the 100-year post-development peak flows will be reduced to the 2-year pre-development peak flows. Using the allowable release rate of **83.2 L/s/ha**, the release rate for each block can be determined as follows:

Since 100-year flows are being considered, the runoff coefficient is multiplied by the MTO factor of 1.25, to a maximum value of 1. Applying the Modified Rational method, the storage required to maintain the prescribed release rate is found. The storage rate per area required for impervious surfaces (C=1.00) is 303 m<sup>3</sup>/ha.

**Table 4: Summary of Modified Rational Method Calculations**

Block ID	Area (ha)	Runoff Coefficient	t <sub>c</sub> (min)	Storage Required (m <sup>3</sup> )	Release Rate <sup>1</sup> (m <sup>3</sup> /s)	Storage/ Area <sup>2</sup> (m <sup>3</sup> /ha)
<b>OUTLET #2</b>						
STREET + BLD A	0.62	1.00	15	188	0.052	303
BLD B	0.49	1.00	15	148	0.041	303
PKNG	0.34	1.00	15	103	0.028	303
FUT.ROW	0.18	1.00	15	54	0.015	303
<b>OUTLET #4</b>						
BLD C + EXT2	0.48	1.00	15	145	0.040	303
<b>TOTAL</b>	<b>2.11</b>			<b>639</b>	<b>0.176</b>	

<sup>1</sup> Release Rate is based on 83.2 L/s/ha (allowable release rate based on pre-development conditions)

<sup>2</sup> Storage/ Area is calculated by taking the Storage Required and dividing by block area

The Modified Rational Method calculations can be found in **Appendix C**.



For the proposed development, stormwater management strategies will be individually chosen and designed for each of the blocks during detailed design. Subsequent Site Plan Applications will be submitted once the process is further advanced. One feasible option for quantity control is to direct runoff into underground storage tanks. Storage requirement for the future municipal ROW is also provided in an underground storage tank, whereas an oversized pipe may be more feasible and will be further contemplated in future design stages. The tank layouts are shown in **Figure 9 – Stormwater Management Plan** and **Figure 10 – Post-Development Drainage Plan**.

The approximate dimensions of underground storage tanks are provided in Table 5 below.

**Table 5: Underground Storage Tanks**

Block ID	Storage Required (m <sup>3</sup> )	Tank Depth <sup>1</sup> (m)	Tank Footprint (m <sup>2</sup> )
<b>OUTLET #2</b>			
<b>STREET + BLD A</b>	188	2.0	94
<b>BLD B</b>	148	2.0	74
<b>PKNG</b>	103	0.5	206
<b>FUT.ROW</b>	54	2.5	22
<b>OUTLET #4</b>			
<b>BLD C + EXT2</b>	145	3.0	48
<b>TOTAL</b>	<b>639</b>		
<sup>1</sup> As per the section views of the Site Plan, parking (P1) level is 5 m high. Considering the Building FFEs, the slab thickness, and the presence of exposed foundations, 2 - 3 m is approximated as the available storage tank depth for the tanks proposed in the parking levels. For the tanks proposed under parking lots or within the ROW, the depth is approximated based on the proposed surface grades, tank inverts, and typical cover for pavement.			

Flows from each of these blocks will be controlled by an orifice. The total allowable release rate for Outlets #2 and #4 is 176 L/s.

**Table 6: Orifice Plate Sizes**

Block ID	Release Rate (m <sup>3</sup> /s)	Orifice Plate Invert (m)	Acting Head (m)	Orifice Size (mm)
<b>OUTLET #2</b>				
<b>STREET + BLD A</b>	0.052	100.33	2.0	130
<b>BLD B</b>	0.041	100.46	2.0	115
<b>PKNG</b>	0.028	100.25	0.5	140
<b>FUT.ROW<sup>1</sup></b>	0.136	99.52	2.5	200
<b>OUTLET #4</b>				
<b>BLD C + EXT2</b>	0.040	100.29	3.0	100
	<b>0.176</b>			
<sup>1</sup> The storage tank for 'FUT.ROW' is located along the storm sewers that drain to Outlet #2. The orifice downstream of this tank (at MH2) will receive controlled flows from Building A ('BLD A'), Building B ('BLD B'), a portion of Private Street A ('STREET') and future parking area ('PKNG'). The orifice will restrict peak flows to 136 L/s for the total drainage area of 1.63 ha.				

### 6.5.3 STORM SEWER DESIGN

The minor storm sewer system will be designed to convey the 10-yr storm flows. The storm sewer layout includes servicing stubs for the expected development blocks.

### 6.5.4 QUALITY CONTROL

The City of Mississauga's objective of 80% TSS removal applies to the Site. Most of the development blocks consist of "clean" surfaces that will not impair stormwater quality downstream of the Site such as roof and pedestrian/landscaped courtyard, i.e., there is little opportunity for these surfaces to be "dirty". Sediment generation is not expected to be significant for pedestrian at-grade hardscape areas. The community park block is also considered "clean" as it will mostly consist of grassed areas. Quality control would be required for impervious surfaces that generate pollutants such as parking lots and streets.

#### Residential Development Blocks

Drainage from the development blocks will receive 80% TSS removal through a combination of LIDs prior to discharging to the private streets or future municipal ROW. The location and composition of the LIDs within the development blocks will be finalized during the Site Plan approval stage. The following are some feasible LID strategies:

- **Bioretention:** Bioretention is a stormwater infiltration practice that treats runoff from paved areas by using the natural properties of soil and vegetation to remove contaminants. Most are designed as swales or islands and are constructed adjacent to roads, parking lots or other paved areas. Runoff from these impervious surfaces are directed into the bioretention area, where it ponds and slowly infiltrates. According to LID Treatment Train Tool by created by STEP, bioretention may provide **75% TSS removal**.
- **Grassed swales:** Grass swales are shallow sloped, densely vegetated channels designed to treat stormwater runoff. As water flows through the channel, vegetation slows the water and allows for sedimentation and filtering of pollutants through the subsoil. According to LID Treatment Train Tool created by STEP, enhanced swales may provide **40% TSS removal**.
- **Permeable pavement:** Permeable pavement help to restore natural infiltration functions to the landscape and reduce impacts to watercourses by allowing rainwater to slowly infiltrate into the ground. Contaminants are removed from the stormwater as it infiltrates slowly through the gravel sub-base and into the native soil. According to LID Treatment Train Tool created by STEP, permeable pavements may provide **75% TSS removal**.
- **Green roofs:** Green roofs are contained areas of vegetation, such as grasses or shrubs, that can be planted on top of buildings. Although green roofs are not credited any TSS removal as of now, they provide many benefits beyond stormwater quality control.
- **Oil Grit Separators (OGS):** OGS units are devices that collect debris, sediment and hydrocarbons from runoff and capture these pollutants in the device's sump rather than conveying these downstream. An OGS will be provided for each development block prior to runoff entering the storage tanks. Refer to **Figure 4 – General Servicing Plan** for placement of the OGS units. The sizing of the OGS units will be specified in the detailed design stage accordingly. Generally, OGS units are credited **50% TSS removal**.



### **Future Municipal ROW**

In Block 6, four bioswales are proposed. Bioswales can be used to filter and retain stormwater runoff. They have a filter media bed that encourages treatment and infiltration of stormwater runoff. During detailed design, these bioswales will be sized with appropriate footprint and depth in order to retain 5 mm of runoff from the ROW. According to LID Treatment Train Tool created by STEP, bioswales may provide **75% TSS removal**.

Additionally, an OGS is proposed downstream of MH1 that will treat runoff from the future municipal ROW. Refer to **Figure 4 – General Servicing Plan** for placement of the OGS unit. The sizing of the OGS unit will be specified in the detailed design stage accordingly. Generally, OGS units are credited **50% TSS removal**.

### **Infiltration Considerations**

A geotechnical and hydrogeological report was prepared by Grounded Engineering Inc. in February 2024. The hydraulic conductivity across the Site ranges from  $1.5 \times 10^{-9}$  m/s (clayey silt, some sand) up to  $1.7 \times 10^{-5}$  m/s (gravelly sand). As per Appendix C - Site Evaluation and Soil Testing Protocol for Stormwater Infiltration provided by the Toronto and Region Conservation Authority Stormwater Management Criteria Guidelines (August 2012), hydraulic conductivity can be converted to infiltration rates, resulting in rates between 8 mm/hr to 98 mm/hr. The groundwater depth was observed in December 2020 and January 2023, and ranged from 1.9 m to 3.5 mbgs. Infiltration opportunities are limited in the development blocks given the extent of the underground parking. However, infiltration-based techniques for individual blocks will be contemplated in future design stages, provided there is available footprint and depth to accommodate these facilities.

### **6.5.5 WATER BALANCE**

Each block is required to retain 5mm of rainfall for the purpose of water balance. Given that the pre-development condition mostly consists of impervious surfaces, there will not be an infiltration deficit in the post-development condition. Rather, the water balance criteria will help to reduce runoff volume in the storm sewer system downstream.

This can be achieved through a combination of LID strategies, such as bioretention, grassed swales, and permeable pavements. While this will be discussed in detail in individual Site Plan Applications, it is important to note that high surface imperviousness, underground parking requirements, and low hydraulic conductivity of the underlying soil might make it difficult for the development blocks to achieve this target. One feasible option to achieve water balance within the development blocks is to harvest rainwater for reuse for irrigation purposes, potentially for the landscaped areas or green roofs on site. Where stormwater storage tanks are proposed, the required water balance volume can be located beneath the storm outlet invert as part of the sump to allow for reuse. Within the future municipal ROW, bioswales are proposed to capture and infiltrate stormwater runoff. For the community park, natural surface depressions and topsoil amendments can encourage infiltration of runoff, particularly for the common low-intensity storms.

The water balance requirement for each drainage area is provided in Table 7.

**Table 7: 5mm Water Balance Requirement**

Block ID	Area (ha)	Retention Requirement (m <sup>3</sup> )
<b>OUTLET #2</b>		
STREET + BLD A	0.62	31.0
BLD B	0.49	24.5
PKNG	0.34	17.0
FUT.ROW	0.18	9.0
<b>OUTLET #4</b>		
BLD C + EXT2	0.48	24.0
<b>TOTAL</b>	<b>2.11</b>	<b>105.5</b>

Water balance measures are not proposed in drainage areas 'EXT104', 'MTO1' and 'MTO2'.

## 7.0 DEWATERING ASSESSMENT

A hydrogeological report by Grounded Engineering (February 15, 2024) summarizes the groundwater water quality and dewatering options.

### Water Quality

A groundwater sample was collected on January 30, 2023. The groundwater sample met the Limits for Sanitary and Combined Sewer Discharge for all parameters analyzed; however, the Region of Peel does not allow permanent groundwater to discharge into the sanitary sewer. The groundwater sample exceeded the Limits for Storm Sewer Discharge for Total Suspended Solids, Total Kjeldahl Nitrogen, and some metals.

### Private Water Drainage System (PWDS)

If the proposed development consists of drained foundations, then a private water drainage system will be required. If the proposed development is designed as a watertight structure, then a private water drainage system will not be required; however, the structure must then be designed to resist hydrostatic pressure and uplift forces. There will be no permanent groundwater dewatering discharge from the development.



## 8.0 CONCLUSION

We trust that this report sufficiently addresses the Site servicing requirements and that the proposed development is feasible from municipal servicing and stormwater management perspectives. In summary:

### Sanitary Servicing:

- The proposed development will outlet to the new 450 mm sanitary sewer on Haig Boulevard.
- The sanitary sewer flows outletting to Haig Boulevard will increase by 30 L/s (47.1 – 17.1) over the pre-development conditions.

### Water Servicing:

- The proposed development will connect to the 300mm watermain on South Service Road and the 200mm watermain on Haig Boulevard.
- Peak hour demand = 26.17 L/s
- Fire flow is calculated based on MOE Design Guidelines for Drinking-Water Systems. Maximum Fire Flow Demand + Peak Daily Demand = 122.45 L/s

### Stormwater Servicing:

- The proposed development contains storm sewers, with four outlets (two new connections) to the existing box culvert, which discharges to Applewood Creek.

### Runoff Quantity Control:

- No quantity control is proposed for Outlets #1 and #3 drainage areas.
- For Outlets #2 and #4, the 100-year post-development peak flows are reduced to the 2-year pre-development flows of 0.136 m<sup>3</sup>/s and 0.040 m<sup>3</sup>/s, respectively.
- Quantity control for the development blocks and streets will be individually chosen and designed at the SPA stage. Approximately 493 m<sup>3</sup> and 145 m<sup>3</sup> of storage is proposed in underground storage tanks for the drainage areas of Outlets #2 and #4, respectively.

### Post Development Quality Control:

- Quality control for the blocks can be provided through a variety of LID measures, where the combination equates 80% TSS removal.
- A combination of LIDs, which will be finalized for each Site plan block during the Site Plan approval stage, can be used. Some feasible options include bioretention, grassed swales, permeable pavements, and green roofs. An OGS is proposed for each development block prior to runoff entering the storage tanks.
- Bioswales and an OGS unit are proposed in the future municipal ROW.
- Quality control is not required for the “clean” surfaces that will not impair stormwater quality.

### Water Balance:

- Within the development blocks, water balance will be achieved by harvesting rainwater for reuse for irrigation purposes, potentially for the landscaped areas or green roofs on Site.
- In the future municipal ROW, bioswales can be utilized to meet the water balance requirements.



Please do not hesitate to contact the undersigned if you have any questions or concerns.

Yours very truly,

KWA Site Development Consulting Inc.



Per:

Pavneet Brar, P.Eng., MASC

[pavneet.brar@kwasitedev.com](mailto:pavneet.brar@kwasitedev.com)



Carlo Del Buono, P. Eng., LEED AP

[carlo.delbuono@kwasitedev.com](mailto:carlo.delbuono@kwasitedev.com)

# **APPENDIX A**

## SANITARY DEMAND CALCULATIONS



## Sanitary Demands - Existing

**Project Name:** Dixie Outlet Mall  
**Project Number:** 19410  
**Location:** Mississauga, Ontario  
**Date:** 10-Apr-24  
**Prepared by:** PB

**Infiltration Allowance + Foundation Drain Allowance** 0.000280 m3/sec/ha

Flow Data		
Type of Development	Equivalent Population (ppl / ha)	Rate (Litres / cap / day)
Single family (greater than 10m frontage)	50	290
Single family (less than 10m frontage)	70	290
Semi-detached	70	290
Row dwellings	175	290
Apartments	475	290
Commercial	50	270
Light Industrial	70	270

Description	Outlet	Commercial Land Area for Equiv Pop (ha)	Total Land Area (ha)	Commercial Population	Total Population *	Average Flow (L/s)
Commercial	Haig	19.60	19.60	980	980	3.06
<b>Total</b>		<b>19.60</b>	<b>19.60</b>	<b>980</b>	<b>980</b>	<b>3.06</b>

### Flows to Haig Blvd

**Total Average Flow = 3.06 L/s**  
**Peaking Factor = 3.81**  
**Peak Flow = 11.65 L/s**  
**Infiltration = 5.49 L/s**  
**Total Sanitary Flow = 17.14 L/s**

### Existing Capacity Check: Sewer on Haig Blvd

**Existing 900 mm Pipe Capacity @ 0.6% = 1463.00 L/s**  
**Required/ Available = 1%**

## Sanitary Demands - Remaining Dixie Outlet Mall Flows

**Project Name:** Dixie Outlet Mall  
**Project Number:** 19410  
**Location:** Mississauga, Ontario  
**Date:** 10-Apr-24  
**Prepared by:** PB

**Infiltration Allowance + Foundation Drain Allowance** 0.000280 m3/sec/ha

Flow Data		
Type of Development	Equivalent Population (ppl / ha)	Rate (Litres / cap / day)
Single family (greater than 10m frontage)	50	290
Single family (less than 10m frontage)	70	290
Semi-detached	70	290
Row dwellings	175	290
Apartments	475	290
Commercial	50	270
Light Industrial	70	270

Description	Outlet	Commercial Land Area for Equiv Pop (ha)	Total Land Area (ha)	Commercial Population	Total Population *	Average Flow (L/s)
Commercial	Haig	16.90	16.90	845	845	2.64
<b>Total</b>		<b>16.90</b>	<b>16.90</b>	<b>845</b>	<b>845</b>	<b>2.64</b>

### Flows to Haig Blvd

<b>Total Average Flow =</b>	<b>2.64</b>	<b>L/s</b>
<b>Peaking Factor =</b>	<b>3.85</b>	
<b>Peak Flow =</b>	<b>10.16</b>	<b>L/s</b>
<b>Infiltration =</b>	<b>4.73</b>	<b>L/s</b>
<b>Total Sanitary Flow =</b>	<b>14.89</b>	<b>L/s</b>



## Sanitary Demands - Phase 1

**Project Name:** Dixie Outlet Mall  
**Project Number:** 19410  
**Location:** Mississauga, Ontario  
**Date:** 10-Apr-24  
**Prepared by:** CDB/ PB

**Infiltration Allowance + Foundation Drain Allowance** 0.000280 m3/sec/ha

Flow Data		
Type of Development	Equivalent Population (ppl / ha)	Rate (Litres / cap / day)
Single family (greater than 10m frontage)	50	290
Single family (less than 10m frontage)	70	290
Semi-detached	70	290
Row dwellings	175	290
Apartments	475	290
Commercial	50	270
Light Industrial	70	270

Description	Outlet	Total Land Area (ha)	# Apartment (1 Bedroom)	# Apartment (2 Bedroom)	# Apartment (3 Bedroom)	Total Apartment Units	Total Population *	Average Flow (L/s)
1	Haig	0.56	103	32	24	159	429	1.44
2	Haig	0.68	220	68	51	338	913	3.06
3	Haig	0.71	325	100	75	500	1350	4.53
4	Park	0.46				0	0	0.00
5	Easement	0.14				0	0	0.00
6	ROW	0.15				0	0	0.00
<b>Total</b>		<b>2.70</b>	<b>648</b>	<b>199</b>	<b>150</b>	<b>997</b>	<b>2692</b>	<b>9.04</b>

\* Townhouse and Apartment populations calculated based on 2.7 people / unit

### Flows to Haig

<b>Total Average Flow =</b>	<b>9.04</b>	<b>L/s</b>
<b>Peaking Factor =</b>	<b>3.48</b>	
<b>Peak Flow =</b>	<b>31.46</b>	<b>L/s</b>
<b>Infiltration =</b>	<b>0.76</b>	<b>L/s</b>
<b>Total Sanitary Flow =</b>	<b>32.22</b>	<b>L/s</b>

### Capacity Check: Sewer on Haig Blvd

<b>Flow required =</b>	<b>47.1</b>	<b>L/s</b>
<b>450 Pipe Capacity @ 0.155%</b>	<b>111</b>	<b>L/s</b>
<b>Required/ Available =</b>	<b>42%</b>	

# Pavneet Brar

**Subject:** FW: 1250 South Service Road - G.E. Booth Wastewater Treatment Plant Capacity

**From:** Carlo Del Buono <carlo.delbuono@kwasitedev.com>

**Sent:** Thursday, April 4, 2024 4:40 PM

**To:** Frandsen, Iwona <iwona.frandsen@peelregion.ca>; Pavneet Brar <Pavneet.Brar@kwasitedev.com>

**Cc:** Simms, Joy <joy.simms@peelregion.ca>; Budathoki, Roshia <rosha.budathoki@peelregion.ca>

**Subject:** RE: 1250 South Service Road - G.E. Booth Wastewater Treatment Plant Capacity

Hi Iwona,

Thanks for the reply and great to hear that we can connect into the new 450mm sewer on Haig.

As you noted crossing the existing storm box culvert to outlet sanitary flows to Dixie is the issue for this site. This is why we need the entire northwest site area sanitary flows to drain to Haig. Any future development southeast of the box culvert is envisioned to outlet to the Dixie trunk sewer. See below image showing the delineation of future development areas. Future development area shown in orange to outlet to Haig. Future development area shown in blue to outlet to Dixie.





You are correct, the existing mall is all being pumped to Haig. We envision this outlet location being maintained in the future development of the northwest block shown in orange. Once future development phases unfold within the southeast block and more of the existing mall is removed, at this time is when a new sanitary connection to Dixie will be made and this area will outlet to the Dixie trunk sewer.

Can you quantify the downstream capacity constraint in the Haig Sewer? How much flows from the northwest block are allowed to drain to the Haig Sewer?

Thanks Iwona

Carlo Del Buono, P. Eng., LEED AP  
KWA Site Development Consulting Inc.  
(416) 821-5625  
[carlo.delbuono@kwasitedev.com](mailto:carlo.delbuono@kwasitedev.com)  
[www.kwasitedev.com](http://www.kwasitedev.com)



---

NOTE: This e-mail is intended only for the named recipient(s) above and may contain information that is privileged and/or confidential . If you have received this message in error, or are not the named recipient(s), please notify the sender immediately and delete this e-mail.

---

**From:** Frandsen, Iwona <[iwona.frandsen@peelregion.ca](mailto:iwona.frandsen@peelregion.ca)>  
**Sent:** Thursday, April 4, 2024 10:58 AM  
**To:** Carlo Del Buono <[carlo.delbuono@kwasitedev.com](mailto:carlo.delbuono@kwasitedev.com)>; Pavneet Brar <[Pavneet.Brar@kwasitedev.com](mailto:Pavneet.Brar@kwasitedev.com)>  
**Cc:** Simms, Joy <[joy.simms@peelregion.ca](mailto:joy.simms@peelregion.ca)>; Budathoki, Rosha <[rosha.budathoki@peelregion.ca](mailto:rosha.budathoki@peelregion.ca)>  
**Subject:** RE: 1250 South Service Road - G.E. Booth Wastewater Treatment Plant Capacity

Hi Bruno,

Your initial proposal was to connect to the 900mm on Haig so connection to 450 is ok too, I will ask about the new MH installation on the 450, there maybe associated cost is that ok? and plan provide drawing WS-14 , if available, and get back to you.

Can you divert phase 2 to Dixie sani sewers? I know that there are capacity constraints beyond Phase 1 downstream on Haig Sewer. Plus there is the storm culvert. I think the mall effluent is being pumped to Haig, can those flows be diverted to Dixie sewer as well?

Thank you,

Iwona Frandsen

Project Manager – Servicing Connections  
Planning & Development Services,  
Public Works,  
Region of Peel

10 Peel Centre Drive, Suite B, 4th Floor (currently working off site) Brampton, On L6T 4B9  
e-mail: [iwona.frandsen@peelregion.ca](mailto:iwona.frandsen@peelregion.ca)  
phone: 905-791-7800 ext 7920

*In response to the emergence of the novel coronavirus, the Region of Peel is implementing various measures to protect our customers, employees and workplaces. Development Services will endeavour to maintain the continuity of our business operations, however delays in service may still be experienced. We appreciate your patience during this time.*

This e-mail is for the sole use of the intended recipient and may contain confidential or privileged information. Unauthorized use of its contents is prohibited. If you have received this e-mail in error, please notify sender immediately via return e-mail and then delete the original e-mail.

---

**From:** Carlo Del Buono <[carlo.delbuono@kwasitedev.com](mailto:carlo.delbuono@kwasitedev.com)>  
**Sent:** Monday, April 1, 2024 4:31 PM  
**To:** Frandsen, Iwona <[iwona.frandsen@peelregion.ca](mailto:iwona.frandsen@peelregion.ca)>; Pavneet Brar <[Pavneet.Brar@kwasitedev.com](mailto:Pavneet.Brar@kwasitedev.com)>  
**Cc:** Simms, Joy <[joy.simms@peelregion.ca](mailto:joy.simms@peelregion.ca)>; Budathoki, Rosha <[rosha.budathoki@peelregion.ca](mailto:rosha.budathoki@peelregion.ca)>  
**Subject:** RE: 1250 South Service Road - G.E. Booth Wastewater Treatment Plant Capacity

**CAUTION: EXTERNAL MAIL. DO NOT CLICK ON LINKS OR OPEN ATTACHMENTS YOU DO NOT TRUST.**

Hi Iwona,  
Thanks for sharing the additional information on Haig Boulevard. This is the first we are seeing the 450mm sanitary sewer running parallel to the new 900mm trunk sewer along Haig.

Attached is our current servicing layout we are contemplating for Phase 1. We are updating our base file to show the new 450mm and 900mm sanitary sewer on Haig Boulevard based on WS-20/WS-21 provided. Our current design does not contemplate the sanitary sewer extension on South Service Road any longer. Based on the alignment of MH37, this will be a challenge. We are going back to the original layout proposing a watermain/sanitary easement within the private road.

Based on the future access public right of way contemplated off Haig Boulevard, would it be possible to add a new MH approximately **50m south** of SAN MHB1 from drawing WS-21. This to ensure we have a connection point to the 450mm sanitary sewer on Haig Boulevard.

We see that the 450mm sanitary sewer connects to the 900mm trunk sewer downstream. For Phase 1, the applicant is proposing approximately +/- 1000 units. Although future build out of Phase 2 in this area has not been confirmed, we have assumed another +/-1000 units would be contemplated to outlet to the Haig sanitary sewer.

Can the Region confirm if the 450mm/900mm sanitary trunk sewer on Haig has the capacity to support the following sanitary flows:

- Phase 1 + Existing Mall = 35 L/s + 15 L/s = **50 L/s**
- Phase 2 = **30 L/s**
  - Total Sanitary Flows to Haig Boulevard = **80 L/s**

Also, would the Region be able to provide drawing WS-14 so we show the proper alignment of the new 400mm watermain on South Service Road.

Thanks Iwona.



Carlo Del Buono, P. Eng., LEED AP  
KWA Site Development Consulting Inc.  
(416) 821-5625  
[carlo.delbuono@kwasitedev.com](mailto:carlo.delbuono@kwasitedev.com)  
[www.kwasitedev.com](http://www.kwasitedev.com)



---

NOTE: This e-mail is intended only for the named recipient(s) above and may contain information that is privileged and/or confidential . If you have received this message in error, or are not the named recipient(s), please notify the sender immediately and delete this e-mail.













METRIC DIMENSIONS ARE IN METRES AND/OR MILLIMETRES UNLESS OTHERWISE SHOWN



Ontario Ministry of Transportation logo and project information including Cont No, GWP No, and sheet details.






AECOM logo

PLEASE NOTE: THIS DRAWING IS NOT MARKED 'AS-CONSTRUCTED'



- NOTES: 1. CONTRACTOR TO PROVIDE DETAILS FOR BULKHEADS FOR INCOMING AND OUTGOING PIPES... 2. ALL EXISTING SANITARY LATERALS TO BE RECONNECTED TO NEW 450mm SANITARY SEWER...

DISCLAIMER These records are based upon available and unverified information and may prove inaccurate. The Region of Peel disclaims any responsibility should these records be relied upon to the detriment of any person.



Professional Engineer seal for A.S. Hundal, dated 2023-04-05, and a revision table.

Table with columns: REVISIONS, DATE, BY, DESCRIPTION. Contains four revision entries for realigned sewer and pipe class changes.



# **APPENDIX B**

## WATER DEMAND CALCULATIONS



## Water Demands - Phase 1

**Project Name:** Dixie Outlet Mall  
**Project Number:** 19410  
**Location:** Mississauga, Ontario  
**Date:** 12-Apr-24  
**Prepared by:** PB

Type of Development	Flow Data Equivalent Population (ppl / ha)	Units	Max Day Factor	Peak Hour Factor
Single family (greater than 10m frontage)	50	L / cap / day	2	3
Single family (less than 10m frontage)	70	L / cap / day	2	3
Semi-detached	70	L / cap / day	2	3
Row dwellings	175	L / cap / day	2	3
Apartments	475	L / cap / day	2	3
Commercial	50	L / employee / day	1.4	3
Light Industrial	70	L / employee / day	1.4	3

Description	Commercial GFA for Equiv Pop (ha)	Total Land Area (ha)	# Apartment (1 Bedroom)	# Apartment (2 Bedroom)	# Apartment (3 Bedroom)	Total Apartment Units	Total Units (Apartment + Townhouses)	Apartment Flows			
								Apartment Population *	Apartment Average Flow (L/s)	Apartment Max Day (L/s)	Apartment Peak Hour (L/s)
1	Haig	0.56	103	32	24	159	159	429	1.39	2.78	4.17
2	Haig	0.68	220	68	51	338	338	913	2.96	5.92	8.87
3	Haig	0.71	325	100	75	500	500	1350	4.38	8.75	13.13
4	Park	0.46				0	0	0	0.00	0.00	0.00
5	Easement	0.14				0	0	0	0.00	0.00	0.00
6	ROW	0.15				0	0	0	0.00	0.00	0.00
<b>Total</b>		<b>2.70</b>	<b>648</b>	<b>199</b>	<b>150</b>	<b>997</b>	<b>997</b>	<b>2692</b>	<b>8.72</b>	<b>17.45</b>	<b>26.17</b>

\* Townhouse and Apartment populations calculated based on 2.7 people / unit



## Fire Flow Demand

**Project Name:** Dixie Outlet Mall  
**Project Number:** 19410  
**Location:** Mississauga, Ontario  
**Date:** 28-Mar-24  
**Prepared by:** PB

From MOE's Design Guidelines for Drinking-Water Systems

**Table 8-1: Fire Flow Requirements**

EQUIVALENT POPULATION <sup>1</sup>	SUGGESTED FIRE FLOW (L/s)	DURATION (HOURS)
500 – 1 000	38 (10 ft/s)	2
1 000	64 (17 ft/s)	2
1 500	79 (21 ft/s)	2
2 000	95 (25 ft/s)	2
3 000	110 (29 ft/s)	2
4 000	125 (33 ft/s)	2
5 000	144 (38 ft/s)	2
6 000	159 (42 ft/s)	3
10 000	189 (50 ft/s)	3
13 000	220 (58 ft/s)	3
17 000	250 (66 ft/s)	4
27 000	318 (84 ft/s)	5
33 000	348 (92 ft/s)	5
40 000	378 (100 ft/s)	6

Note <sup>1</sup>: When determining the fire flow allowance for commercial or industrial areas, it is recommended that the area occupied by the commercial/industrial complex be considered at an equivalent population density to the surrounding residential lands.

**Excerpt from Table 8-1**

Pop	Fire Flow (L/s)	Duration (hrs)
2000	95	2
3000	110	2

**Interpolation for equivalent population**

2692	105	2.00
------	-----	------



**Region of Peel Multi-Use Demand Table**

**WATER CONNECTION**

<b>Connection Point:</b>	400 mm watermain on South Service Road and 200 mm watermain on Haig Boulevard	
<b>Pressure zone of connection point</b>	Pressure Zone 1 (CT1)	
	<b>Residential</b>	<b>Total</b>
<b>Total equivalent population to be serviced</b>	2692	2692
<b>Total lands to be serviced</b>	2.70	2.70

**Hydrant Flow Test**

Hydrant Flow Test Location 1
1250 South Service Rd, Mississauga, ON (along South Service Road)

	Pressure (psi)	Flow (L/s)	Time
Minimum water pressure	61	100	8:30 AM
Maximum water pressure	64	0	8:30 AM

No.	Demand Type	Water demands	
		Residential	Total
1	Average day flow (L/s)	8.72	8.72
2	Maximum day flow (L/s)	17.45	17.45
3	Peak hour flow (L/s)	26.17	26.17
4	Fire flow (L/s)	105	105
		Analysis	
5	Maximum day plus fire flow (L/s)	122.45	122.45
6	Peak hour flow (L/s)	26.17	26.17
7	Maximum demand flow (L/s)	122.45	122.45

**WASTEWATER CONNECTION**

<b>Connection Point</b>	450 mm sanitary sewer on Haig Blvd flowing at 0.155%	
<b>Total Lands to be serviced (ha):</b>	2.70 (new development) + 16.90 (existing mall) = 19.60 ha	
<b>Total equivalent population to be serviced:</b>	<b>Residential</b>	845
	<b>Non-Residential</b>	2692
	<b>Total</b>	3537
<b>8 Wastewater Sewer Effluent (m<sup>3</sup>/s):</b>	<b>Total</b>	0.0471



# **APPENDIX C**

## **STORMWATER MANAGEMENT CALCULATIONS**



### Rational Method (Pre-Development Condition) - Outlet #2

Project No:		19410
Project Name:		Dixie Mall
Storm Event:		2 years
ABC's:	a	610
	b	4.6
	c	0.78
Time of Concentration:	t	15 min
Runoff Coefficient:	C	0.5
Site Area	A	1.63 ha
Intensity [ $i=a/(t+b)c$ ] or [ $i=a*tb$ ] if B=0	i	59.89 mm/hr
Flow [Q=CiA/360]	Q	0.14 m <sup>3</sup> /s
		136 L/s
Proposed Area (draining to box culvert)		1.63 ha
Flow Rate per hectare		83.2 L/s/ha

### Rational Method (Pre-Development Condition) - Outlet #4

Project No:		19410
Project Name:		Dixie Mall
Storm Event:		2 years
ABC's:	a	610
	b	4.6
	c	0.78
Time of Concentration:	t	15 min
Runoff Coefficient:	C	0.5
Site Area	A	0.48 ha
Intensity [ $i=a/(t+b)c$ ] or [ $i=a*tb$ ] if B=0	i	59.89 mm/hr
Flow [Q=CiA/360]	Q	0.04 m <sup>3</sup> /s
		40 L/s
Proposed Area (draining to box culvert)		0.48 ha
Flow Rate per hectare		83.2 L/s/ha



## Modified Rational Calculation

Project Name: Dixie Mall  
 Project Number: 19410

Rainfall Data			
Location:	Mississauga	a	1450.00
Event	100	b	4.90
		c	0.78

Block ID	Area (ha)	Runoff Coefficient	$t_c$ (min)	Storage Required (m <sup>3</sup> )	Release Rate <sup>1</sup> (m <sup>3</sup> /s)	Storage/ Area <sup>2</sup> (m <sup>3</sup> /ha)
<b>OUTLET #2</b>						
STREET + BLD A	0.62	1.00	15	188	0.052	303
BLD B	0.49	1.00	15	148	0.041	303
PKNG	0.34	1.00	15	103	0.028	303
FUT.ROW	0.18	1.00	15	54	0.015	303
<b>OUTLET #4</b>						
BLD C + EXT2	0.48	1.00	15	145	0.040	303
<b>TOTAL</b>	<b>2.11</b>			<b>639</b>	<b>0.176</b>	

<sup>1</sup> Release Rate is based on 83.2 L/s/ha (allowable release rate based on pre-development conditions)

<sup>2</sup> Storage/ Area is calculated by taking the Storage Required and dividing by block area

Flow Rate per hectare **83.2** L/s/ha





**Modified Rational**                      **Area:**     **STREET + BLD A**

Project Name:        Dixie Mall  
 Project Number:        19410

Rainfall Data			
Location:	Mississauga	a	1450.000
Event	100	b	4.900
		c	0.780

Site Data	
Area	0.62 ha
Runoff Coefficient	1.00
AC	0.62
Tc	15
Time Increment	10
Release Rate	52 l/s
Storage Required	188 m <sup>3</sup>

Time (min)	Rainfall Intensity (mm/hr)	Storm Runoff (m3/s)	Runoff Volume (m3)	Released Volume (m3)	Storage Volume (m3)	
15	141	0.24	218	46	172	
25	102	0.18	265	77	187	
35	82	0.14	296	108	188	*****
45	69	0.12	320	139	180	
55	60	0.10	339	170	169	
65	53	0.09	355	201	154	
75	48	0.08	369	232	137	
85	43	0.07	381	263	118	
95	40	0.07	393	294	99	
105	37	0.06	403	325	78	
115	35	0.06	412	356	56	
125	33	0.06	421	387	34	
135	31	0.05	429	418	11	
145	29	0.05	437	449	-12	
155	28	0.05	444	480	-36	
165	26	0.05	451	511	-60	
175	25	0.04	457	542	-84	
185	24	0.04	463	572	-109	
195	23	0.04	469	603	-134	
205	22	0.04	475	634	-160	
215	22	0.04	480	665	-185	





**Modified Rational**

**Area: BLD B**

Project Name: Dixie Mall  
 Project Number: 19410

Rainfall Data			
Location:	Mississauga	a	1450.000
Event	100	b	4.900
		c	0.780

Site Data	
Area	0.49 ha
Runoff Coefficient	1.00
AC	0.49
Tc	15
Time Increment	10
Release Rate	41 l/s
Storage Required	148 m <sup>3</sup>

Time (min)	Rainfall Intensity (mm/hr)	Storm Runoff (m3/s)	Runoff Volume (m3)	Released Volume (m3)	Storage Volume (m3)	
15	141	0.19	172	37	136	
25	102	0.14	209	61	148	
35	82	0.11	234	86	148	*****
45	69	0.09	253	110	143	
55	60	0.08	268	135	133	
65	53	0.07	281	159	122	
75	48	0.06	292	183	108	
85	43	0.06	301	208	94	
95	40	0.05	310	232	78	
105	37	0.05	318	257	62	
115	35	0.05	326	281	45	
125	33	0.04	333	306	27	
135	31	0.04	339	330	9	
145	29	0.04	345	355	-9	
155	28	0.04	351	379	-28	
165	26	0.04	356	404	-47	
175	25	0.03	361	428	-67	
185	24	0.03	366	452	-86	
195	23	0.03	371	477	-106	
205	22	0.03	375	501	-126	
215	22	0.03	380	526	-146	





**Modified Rational**

**Area: PKNG**

Project Name: Dixie Mall  
 Project Number: 19410

Rainfall Data			
Location:	Mississauga	a	1450.000
Event	100	b	4.900
		c	0.780

Site Data	
Area	0.34 ha
Runoff Coefficient	1.00
AC	0.34
Tc	15
Time Increment	10
Release Rate	28 l/s
Storage Required	103 m <sup>3</sup>

Time (min)	Rainfall Intensity (mm/hr)	Storm Runoff (m3/s)	Runoff Volume (m3)	Released Volume (m3)	Storage Volume (m3)	
15	141	0.13	120	25	94	
25	102	0.10	145	42	103	
35	82	0.08	162	59	103	*****
45	69	0.06	175	76	99	
55	60	0.06	186	93	92	
65	53	0.05	195	110	84	
75	48	0.04	202	127	75	
85	43	0.04	209	144	65	
95	40	0.04	215	161	54	
105	37	0.04	221	178	43	
115	35	0.03	226	195	31	
125	33	0.03	231	212	19	
135	31	0.03	235	229	6	
145	29	0.03	239	246	-7	
155	28	0.03	243	263	-20	
165	26	0.02	247	280	-33	
175	25	0.02	251	297	-46	
185	24	0.02	254	314	-60	
195	23	0.02	257	331	-74	
205	22	0.02	260	348	-87	
215	22	0.02	263	365	-101	





**Modified Rational**                      **Area:**    **FUT.ROW**

Project Name:        Dixie Mall  
 Project Number:        19410

Rainfall Data			
Location:	Mississauga	a	1450.000
Event	100	b	4.900
		c	0.780

Site Data	
Area	0.18 ha
Runoff Coefficient	1.00
AC	0.18
Tc	15
Time Increment	10
Release Rate	15 l/s
Storage Required	54 m <sup>3</sup>

Time (min)	Rainfall Intensity (mm/hr)	Storm Runoff (m3/s)	Runoff Volume (m3)	Released Volume (m3)	Storage Volume (m3)	
15	141	0.07	63	13	50	
25	102	0.05	77	22	54	
35	82	0.04	86	31	54	*****
45	69	0.03	93	40	52	
55	60	0.03	98	49	49	
65	53	0.03	103	58	45	
75	48	0.02	107	67	40	
85	43	0.02	111	76	34	
95	40	0.02	114	85	29	
105	37	0.02	117	94	23	
115	35	0.02	120	103	16	
125	33	0.02	122	112	10	
135	31	0.02	125	121	3	
145	29	0.01	127	130	-3	
155	28	0.01	129	139	-10	
165	26	0.01	131	148	-17	
175	25	0.01	133	157	-24	
185	24	0.01	135	166	-32	
195	23	0.01	136	175	-39	
205	22	0.01	138	184	-46	
215	22	0.01	139	193	-54	





**Modified Rational**

**Area: BLD C + EXT2**

Project Name: Dixie Mall  
 Project Number: 19410

Rainfall Data			
Location:	Mississauga	a	1450.000
Event	100	b	4.900
		c	0.780

Site Data	
Area	0.48 ha
Runoff Coefficient	1.00
AC	0.48
Tc	15
Time Increment	10
Release Rate	40 l/s
Storage Required	145 m <sup>3</sup>

Time (min)	Rainfall Intensity (mm/hr)	Storm Runoff (m3/s)	Runoff Volume (m3)	Released Volume (m3)	Storage Volume (m3)	
15	141	0.19	169	36	133	
25	102	0.14	205	60	145	
35	82	0.11	229	84	145	*****
45	69	0.09	247	108	140	
55	60	0.08	262	132	131	
65	53	0.07	275	156	119	
75	48	0.06	286	180	106	
85	43	0.06	295	204	92	
95	40	0.05	304	228	76	
105	37	0.05	312	252	60	
115	35	0.05	319	276	44	
125	33	0.04	326	299	26	
135	31	0.04	332	323	9	
145	29	0.04	338	347	-9	
155	28	0.04	344	371	-28	
165	26	0.04	349	395	-46	
175	25	0.03	354	419	-65	
185	24	0.03	359	443	-85	
195	23	0.03	363	467	-104	
205	22	0.03	368	491	-124	
215	22	0.03	372	515	-143	



Orifice Control & Detention Storage **Area** **STREET + BLD A**

Orifice Equation:  $Q = C_d A (2gh)^{1/2}$

Orifice Diameter  mm  
 Area: 0.013 m<sup>2</sup>  
 g = 9.81 m/s<sup>2</sup>  
 C<sub>d</sub> =

	Stage	Head (m)	Discharge (m <sup>3</sup> /s)
Invert E.L.	100.33	0.00	0.00
year Ponding E.L.	102.33	1.94	0.051

Orifice Control & Detention Storage **Area** **BLD B**

Orifice Equation:  $Q = C_d A (2gh)^{1/2}$

Orifice Diameter  mm  
 Area: 0.010 m<sup>2</sup>  
 g = 9.81 m/s<sup>2</sup>  
 C<sub>d</sub> =

	Stage	Head (m)	Discharge (m <sup>3</sup> /s)
Invert E.L.	100.46	0.00	0.00
100 year Ponding E.L.	102.46	1.94	0.040

Orifice Control & Detention Storage **Area** **PKNG**

Orifice Equation:  $Q = C_d A (2gh)^{1/2}$

Orifice Diameter  mm  
 Area: 0.015 m<sup>2</sup>  
 g = 9.81 m/s<sup>2</sup>  
 C<sub>d</sub> =

	Stage	Head (m)	Discharge (m <sup>3</sup> /s)
Invert E.L.	100.25	0.00	0.00
year Ponding E.L.	100.75	0.43	0.028

Orifice Control & Detention Storage **Area** **ROW1 + FUTROW**

Orifice Equation:  $Q = C_d A (2gh)^{1/2}$

Orifice Diameter  mm  
 Area: 0.031 m<sup>2</sup>  
 g = 9.81 m/s<sup>2</sup>  
 C<sub>d</sub> =

	Stage	Head (m)	Discharge (m <sup>3</sup> /s)
Invert E.L.	99.52	0.00	0.00
100 year Ponding E.L.	102.02	2.40	0.134

Orifice Control & Detention Storage **Area** **BLD C + EXT2**

Orifice Equation:  $Q = C_d A (2gh)^{1/2}$

Orifice Diameter  mm  
 Area: 0.008 m<sup>2</sup>  
 g = 9.81 m/s<sup>2</sup>  
 C<sub>d</sub> =

	Stage	Head (m)	Discharge (m <sup>3</sup> /s)
Invert E.L.	100.29	0.00	0.00
year Ponding E.L.	103.29	2.95	0.037

-The head is calculated as the difference between ponding elevation and center line of the orifice plate