

7th Floor – 55 St. Clair Avenue West Toronto ON M4V 2Y7 Canada tel 416 596 1930 fax 416 596 0644 arcadis.com

3115 Hurontario Street - Proposed Zoning Table (Revised)

File: OZ/OPA 22-24 W7

Application Type: Official Plan Amendment and Zoning By-law Amendment

It should be noted that the below provisions are subject to change as the planning applications progress. Arcadis Professional Services (Canada) Inc. on behalf of Clearbrook Developments Ltd. reserves the right to modify the below provisions as needed and requests the review of any By-law prior to final approval.

The following Zoning Standards and Regulations shall apply to the site:

BY-LAW SECTION	ZONING STANDARD/ REGULATION	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)
General Pro	visions		
2.1.2.1.1	Min. Separation Distance from Residential Zones	All buildings and structures containing a use in Table 2.1.2.1.1 - Minimum Separation Distance from Residential Zones, shall comply with the applicable minimum separation distance required.	Delete lines 1.0, 2.0 and 3.0 of Table 2.1.2.1.1
2.1.3.1	Frontage on a Street	All lots shall have frontage on a street	N/A - Conforms
2.1.5	Accessory Uses	Where this By-law provides that land may be used or a building or structure may be erected and/or used for a permitted use, that use shall include any building or structure or use accessory thereto as long as the accessory use, building and/or structure is located on the same lot.	N/A – Conforms
2.1.14.1	Min. Centreline Setback	Where a lot abuts a right-of-way or a 0.3 metre reserve abutting a right-of-way identified on Schedules 2.1.14(1) and (2) of this By-law, the minimum distance required between the nearest part of any building or structure to the centreline of the right-of-way shall be as contained in Table 2.1.14.1 - Centreline Setback: Hurontario – 35 m ROW 17.5 m + required yard/setback (within 110 m of intersection)	N/A-Conforms (20.9 m + 2 m setback to building face)

BY-LAW SECTION	ZONING STANDARD/ REGULATION	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)
2.1.30	Rooftop Balcony	A rooftop balcony shall be setback 1.2 m for all exterior edges of a building or structure.	Delete Provision 2.1.30
Parking, Lo	ading, Stacking Lane	and Bicycle Parking Regulations	
3.1.1.4.3	Parking Space Width	The minimum width of a parking space, other than an accessible parking space or parallel parking space, shall be increased to 2.75 m where the length of one side of the parking space abuts a building, structure or part thereof, except for a building, structure or part thereof, that extends 1.0 m or less into the front and/or rear of the parking space.	N/A – Conforms.
3.1.1.5.1	Parking Aisle Width	The minimum aisle width shall be 7.0 m.	N/A - Conforms - Min. Drive Aisle of 7.0 m provided.
3.1.1.5.2	Parking Aisle Width – One Way	Notwithstanding Sentence 3.1.1.5.1, where a one-way aisle is provided for access to and from parking spaces with a parking angle not exceeding 60°, the minimum aisle width may be 5.5 m.	N/A - Conforms.
3.1.2 3.1.2.1	Required Number of Parking Spaces	Table 3.1.2.1 – Residential Uses (Precinct 1)	Residential: 0.23 spaces per unit
3.1.2.2		Condominium Apartment Residential:0.8 resident spaces per unit Visitor: 0.2 visitor spaces per unit Table 3.1.2.2 – Non Residential Uses (Precinct 1) Retail Store: 3.0 spaces per 100 m² GFA Convivence Retail: 3 spaces per less than or equal 220 m² GFA Other Non-Residential Uses Not Specified Above: 5.4 spaces per 100 m² GFA	Visitor: 0.15 spaces per unit
3.1.3 3.1.3.1	Accessible Parking	Table 3.1.3.1 – Accessible Parking Regulations Total Number of Required Visitor Parking Spaces (13-100) – 4% of total	N/A – Conforms.

BY-LAW	ZONING	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)
SECTION	STANDARD/		
	REGULATION		
3.1.4 3.1.4.1	Loading Spaces	Loading spaces shall be required for the following uses: (1) Retail Store	N/A – Conforms.
3.1.4.5		Table 3.1.4.3 – Required Number of Loading Spaces: Less than equal to 250 m ² : None Required	
		Required Number of Loading Spaces for Apartment and/or Retirement Buildings: One loading space per apartment building containing a minimum of 30 dwellings	
3.1.6. 3.1.6.5	Bicycle Parking	Required Number of Bicycle Parking Spaces	N/A – Conforms.
3.1.6.6		 Apartment without exclusive garages: 0.6 spaces per unit 	
		Non-Residential Uses:	
		 Retail: 0.15 spaces per 100 m² GFA non-residential 	
		 All other non-residential uses: 0.05 spaces per 100 m² non- residential GFA 	
4.15 Apartm	nent Zones		
4.1.5.10	Balcony Encroachments	A balcony may encroach a maximum of 1.0 m into a required front, exterior side or rear yard. (0158-2013), (0144-2016)	2.0 m
4.1.15.1.1	Permitted Accessory Uses	Retail store, personal service establishment, financial institution, office and medical office - restricted	The following are to be included as site-specific accessory uses:
			 Charity/Non-Profit Use Retail Personal Service Shop Daycare Education and Training Facility, Restaurant Take-Out Restaurant Recreational Establishment Medical Office Financial Institution Veterinary Clinic

BY-LAW SECTION	ZONING STANDARD/ REGULATION	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)
4.1.15.1.2	Location of Permitted Use	An accessory use shall only be permitted in an apartment having 75 or more dwelling units, or in a long-term care building having 75 or more beds, or in a retirement building having 75 or more retirement dwelling units	Conforms.
4.1.15.1.3	Access to Accessory Use	The accessory use shall be wholly contained within the dwelling and the entrance to the accessory use shall only be from within the dwelling.	Delete Provision.
4.1.15.1.4	Location of Accessory Use	An accessory use shall not be permitted above the first storey of an apartment, retirement building or long-term care building; (0174-2017)	Delete Provision.
4.1.15.1.5	Max GFA - Non- Residential – Accessory Uses	186 m ²	Max. Total GFA non residential – Accessory Uses shall be 1,500 m ²
4.1.15.1.6	Max GFA - Non- Residential for Accessory Uses	Lesser of 10% of the GFA - apartment zone or the GFA - apartment zone of one storey of the dwelling	Max. GFA - non residential accessory uses shall be as follows: - Retail use: 220 m ² - Charity use: 1000 m ²
4.1.15.1.7	Additional On-Site Parking	Not required for accessory uses permitted in 4.1.15.1.1	N/A
4.1.15.3	Height	Notwithstanding any other provisions of this By-law, the calculation of height for apartment, long-term care and retirement buildings, shall be exclusive of mechanical or architectural appurtenances such as mechanical equipment, mechanical penthouse, elevator machine rooms, telecommunication equipment and enclosures, parapets, turrets, cupolas, stairs and stair enclosures, located on the roof of a dwelling provided that the maximum height of the top of such elements is no higher than 6.0 m above the height limit otherwise applicable.	Notwithstanding Provision 4.1.15.3, the max. height of Mechanical or architectural appurtenances above height limit shall be: 9.0 m

BY-LAW SECTION	ZONING STANDARD/ REGULATION	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)		
4.15 RA5	4.15 RA5 Zones (Apartments)				
Table 4.15.1	Permitted Uses	Residential: Apartment, Long-Term Care Building, Retirement Building	Conforms		
Table 4.15.1 3.0	Minimum Lot Frontage	30.0 m	Conforms		
Table 4.15.1	Minimum Floor Space Index	1.9	Conforms		
Table 4.15.1 <i>5.0</i>	Maximum Floor Space Index – Apartment Zone	2.9	12.6		
Table 4.15.1 6.0	Maximum GFA – Apartment Zone per Storey above 12 Storeys	1,000 m ²	Conforms.		
Table 4.15.1	Maximum Height	77.0 m and 25 storeys	133 m (excluding MP) and 42-storeys		
7.0			Max. Height Mechanical Penthouse: 9 m		
Table 4.15.1 8.0 8.1, 8.2, 8.3	Minimum Front and Exterior Side Yards	For that portion of the dwelling with a height less than or equal to 13.0 m: 7.5 m For that portion of the dwelling with a height greater than 13.0 m and less than or equal to 20.0 m: 8.5 m For that portion of the dwelling with a height greater than 20.0 m and less than or equal to 26.0 m: 9.5 m	Min. Front Yard Setback: For portion of the dwelling with a height less than or equal to 13.0 m: 3.0 m For portion of the dwelling with a height greater than 13.0 m and less than or equal to 24.0 m: 3.0 m For that portion of the dwelling with a height greater than 24.0 m and less than or equal to 26.0 m: 6.0 m		
Table 4.15.1 9.0	Minimum Interior Side Yard	For that portion of the dwelling with a height less than or equal to 13.0 m: 4.5 m For that portion of the dwelling with a height greater than 13.0 m and less than or equal to 20.0 m: 6 m	Where an interior side lot line, or any portion thereof, abuts an Apartment, Institutional, Office, Commercial, Employment, or Utility Zone, or any combination of zones thereof: 0.0 m		

BY-LAW SECTION	ZONING STANDARD/	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)
02011011	REGULATION		
9.1, 9.2, 9.3, 9.4, 9.5, 9.6	Minimum Rear	For that portion of the dwelling with a height greater than 20.0 m and less than or equal to 26.0 m: 7.5 m For that portion of the dwelling with a height greater than 26.0 m: 9 m Where an interior side lot line, or any portion thereof, abuts an Apartment, Institutional, Office, Commercial, Employment, or Utility Zone, or any combination of zones thereof: 4.5 m For that portion of the dwelling with a	For that portion of the
4.15.1	Yard	height less than or equal to 13.0 m: 7.5 m	dwelling with a height greater than 20.0 m and less than or equal to 26.0
10		For that portion of the dwelling with a height greater than 13.0 m and less than or equal to 20.0 m: 10.0 m For that portion of the dwelling with a height greater than 20.0 m and less than or equal to 26.0 m: 12.5 m For that portion of the dwelling with a height greater than 26.0 m: 15.0 m Where a rear lot line, or any portion thereof, abuts an Apartment, Institutional, Office, Commercial, Employment, or Utility Zone, or any combination of zones thereof: 4.5 m Where a rear lot line, or any portion thereof, abuts a zone permitting detached dwelling and/or semidetached: 7.5 m plus 1.0 m for each additional 1.0 m of dwelling height, or portion thereof, exceeding 10.0 m to a maximum setback requirement of: 25.5 m"	m: 10.0 m For that portion of the dwelling with a height greater than 26.0 m: 10.0 m
Table 4.15.1 11	Encroachments and Projections	Maximum encroachment of a balcony located above the first storey, sunroom, window, chimney, pilaster, cornice, balustrade or roof eaves into a required yard: 1.0 m Maximum encroachment into a required yard of a porch, balcony	Maximum encroachment of a balcony located above the first storey, sunroom, window, chimney, pilaster, cornice, balustrade or roof eaves into a required yard: 3.0 m
		located on the first storey, staircase, landing or awning, provided that each shall have a maximum width of 6.0 m: 1.8 m Maximum projection of a balcony located above the first storey	Maximum projection of a balcony located above the first storey measured from the outermost face or faces of the building from which the balcony projects: 3.0 m

BY-LAW SECTION	ZONING STANDARD/	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)
	REGULATION		
		measured from the outermost face or faces of the building from which the balcony projects: 1.0 m	
Table 4.15.1 12	Minimum Above Grade Separation Between Buildings	For that portion of dwelling with a height less than or equal to 13.0 m: 3.0 m For that portion of dwelling with a height greater than 13.0 m and less than or equal to 20.0 m: 9.0 m For that portion of dwelling with a height greater than 20.0 m and less than or equal to 26.0 m: 12.0 m	Minimum Grade Separation Distance Between Buildings for that portion of height less than or equal to 26 m shall be: 0.0 m For that portion of dwelling with a height greater than 20.0 m and less than or equal to 26.0 m: 0.0 m
		For that portion of dwelling with a height greater than 26.0 m: 15.0 m	For that portion of dwelling with a height greater than 26.0m: 9.0 m
Table 4.15.1	I – Parking, Loading,	Servicing Area and Parking Structure	
13.2	Minimum setback	Minimum setback from surface	N/A
13.3	from surface parking	parking spaces or aisles to a street line: 4.5 m	
13.4		Minimum setback from surface parking spaces or aisles to any other lot line: 3.0 m Minimum setback from a parking structure above or partially above finished grade to any lot line: 7.5 m	
13.5	Minimum Setback from Below-Grade Parking Structure	Minimum setback from a parking structure completely below finished grade, inclusive of external access stairwells, to any lot line: 3.0 m	0.0 m
13.6	Minimum Setback from Waste Enclosure	Minimum setback from a waste enclosure/loading area to a street line:	Conforms – Enclosure/Loading facing private driveway at rear
Table 14.15.1 – Minimum Landscaped Area, Landscaped Buffer, and Amenity Area			
15.1	Minimum Landscaped Area	40%	10.0%
15.2	Minimum Depth of Landscaped Area	Minimum depth of a landscaped buffer abutting a lot line that is a street line and/or abutting lands with an Open Space, Greenlands and/or a Residential Zone with the exception of an Apartment Zone:	0.0 m along Hurontario Street

BY-LAW SECTION	ZONING STANDARD/ REGULATION	RA5 ZONE REQUIREMENTS	REQUESTED (RA5-XX)
		4.5 m	
15.3	Minimum Depth of Landscaped Area	Minimum depth of a landscaped buffer along any other lot line: 3.0 m	0.0 m
15.4	Minimum amenity area	The greater of 5.6 m² per dwelling unit or 10% of the site area	N/A. Conforms.
15.5	Minimum amenity area provided Contiguously	50%	N/A. Conforms.
15.6	Minimum Amenity Area to be provided outside at-grade	55.0 m ²	0.0 m ²